

## ROUND PERFORATION SIZES

ROUND PERFORATION (INCHES)	OPENING IN DECIMAL	OPENING IN METRIC (MM)
1/25	0.040	1.02
1/24	0.042	1.06
1/23	0.043	1.10
1/22	0.045	1.15
3/64	0.047	1.19
1/21	0.048	1.21
1/20	0.050	1.27
1/19	0.053	1.34
1/18	0.056	1.41
1/17	0.060	1.52
1/16	0.063	1.59
1/15	0.067	1.69
1/14	0.071	1.81
1/13	0.077	1.95
1/12	0.083	2.12
6/64	0.094	2.38
2.5MM	0.098	2.50
6.5/64	0.102	2.58
7/64	0.109	2.78
7.5/64	0.117	2.98
7.75/64	0.121	3.08
8/64	0.125	3.18
8.5/64	0.133	3.37
8.75/64	0.137	3.47
9/64	0.141	3.57
9.5/64	0.148	3.77
9.75/64	0.152	3.87
10/64	0.156	3.97
10.5/64	0.164	4.17
10.75/64	0.168	4.27

<b>11/64</b>	0.172	4.37
<b>11.5/64</b>	0.180	4.56
<b>11.75/64</b>	0.184	4.66
<b>12/64</b>	0.188	4.76
<b>12.5/64</b>	0.195	4.96
<b>13/64</b>	0.203	5.16
<b>13.5/64</b>	0.211	5.36
<b>5.5MM</b>	0.217	5.50
<b>14/64</b>	0.219	5.56
<b>14.5/64</b>	0.227	5.75
<b>14.75/64</b>	0.230	5.85
<b>15/64</b>	0.234	5.95
<b>6MM</b>	0.236	6.00
<b>15.5/64</b>	0.242	6.15
<b>16/64</b>	0.250	6.35
<b>16.5/64</b>	0.258	6.55
<b>17/64</b>	0.266	6.75
<b>17.5/64</b>	0.273	6.95
<b>18/64</b>	0.281	7.14
<b>18.5/64</b>	0.289	7.34
<b>7.5MM</b>	0.295	7.50
<b>19/64</b>	0.297	7.54
<b>19.5/64</b>	0.305	7.74
<b>20/64</b>	0.313	7.94
<b>20.5/64</b>	0.320	8.14
<b>21/64</b>	0.328	8.33
<b>21.5/64</b>	0.336	8.53
<b>22/64</b>	0.344	8.73
<b>22.5/64</b>	0.352	8.93
<b>23/64</b>	0.359	9.13
<b>23.5/64</b>	0.367	9.33
<b>24/64</b>	0.375	9.53
<b>24.5/64</b>	0.383	9.72

---

<b>25/64</b>	0.391	9.92
<b>10MM</b>	0.394	10.00
<b>25.5/64</b>	0.398	10.12
<b>26/64</b>	0.406	10.32
<b>26.5/64</b>	0.414	10.52
<b>27/64</b>	0.422	10.72
<b>27.5/64</b>	0.430	10.91
<b>28/64</b>	0.438	11.11
<b>28.5/64</b>	0.445	11.31
<b>29/64</b>	0.453	11.51
<b>29.5/64</b>	0.461	11.71
<b>30/64</b>	0.469	11.91
<b>30.5/64</b>	0.477	12.10
<b>31/64</b>	0.484	12.30
<b>31.5/64</b>	0.492	12.50
<b>32/64</b>	0.500	12.70
<b>33/64</b>	0.516	13.10
<b>34/64</b>	0.531	13.49
<b>34.5/64</b>	0.539	13.69
<b>35/64</b>	0.547	13.89
<b>35.5/64</b>	0.555	14.09
<b>36/64</b>	0.563	14.29
<b>38/64</b>	0.594	15.08
<b>38.5/64</b>	0.602	15.28
<b>39/64</b>	0.609	15.48
<b>40/64</b>	0.625	15.88
<b>42/64</b>	0.656	16.67
<b>44/64</b>	0.688	17.46
<b>46/64</b>	0.719	18.26
<b>47/64</b>	0.734	18.65
<b>48/64</b>	0.750	19.05
<b>50/64</b>	0.781	19.84
<b>52/64</b>	0.813	20.64

---

<b>54/64</b>	0.844	21.43
<b>55/64</b>	0.859	21.83
<b>56/64</b>	0.875	22.23
<b>57/64</b>	0.891	22.62
<b>58/64</b>	0.906	23.02
<b>64/64</b>	1.000	25.40
<b>1-1/4"</b>	1.250	31.75